

# XEOFIX®

## HD-T 7810



En vente sur [www.aervi-boutique.fr](http://www.aervi-boutique.fr)




### FULL HD DVB-T PVR



260mm X 43mm X 180mm (W x H x D)

- \* Terminal numérique terrestre (TNT) Haute Définition
- \* 2 Accès interface commune (PCMCIA) en CI+
- \* H.264/MPEG4/MPEG-2 (HD/SD), DVB-T
- \* Linux OS Compatible
- \* Enregistrement et Time Shifting sur disque dur externe
- \* Enregistrement simultané de 3 services tout en visionnant 2 autres
- \* PIP (Picture-in-Picture)
- \* Fonction LCN, EPG, Teletexte
- \* HDMI (576i, 576p, 720p, 1080i, 1080p)
- \* Format vidéo supporté (Xvid)
- \* Ethernet 10/100 Mbps (Navigateur internet, accès Youtube, IPTV)
- \* Support Wi-Fi (sur clé usb)
- \* Lecteur de carte (Conax)
- \* Mode économique



En vente sur [www.aervi-boutique.fr](http://www.aervi-boutique.fr)

# XEOFIX®

## HD-T 7810



### FULL HD DVB-T PVR

#### \* Tuner & Channel Decoder (Terrestrial)

|                          |  |
|--------------------------|--|
| <b>Input Connector</b>   | IEC 169-2, Female  |
| <b>Loop through out</b>  | IEC 169-2, Male  |
| <b>Frequency Range</b>   | VHF III : 174~230 MHz<br>UHF IV : 470~606 MHz<br>UHF V : 606~862 MHz |
| <b>Demodulation</b>      | OFDM   |
| <b>Channel Bandwidth</b> | 6, 7, 8 MHz  |
| <b>FET mode</b>          | 1K, 2K, 4K, 8K, 16K, 32K   |
| <b>Code Rate</b>         | 1/2, 2/3, 3/4, 3/5, 4/5, 5/6   |
| <b>Guard Interval</b>    | 1/4, 5/32, 1/8, 5/64, 1/16, 1/32, 1/64, 1/128                        |

#### \* MPEG Transport Stream A/V Decoding

|                         |   |
|-------------------------|---|
| <b>Transport Stream</b> | MPEG-4 part 10(H.264), MPEG-2 ISO/IEC 13818   |
| <b>Profile Level</b>    | MPEG-4 MP@L4.1, MPEG-2 MP@HL  |
| <b>Input Rate</b>       | Max. 80Mbit/s   |
| <b>Video Formats</b>    | 4:3 LetterBox, 4:3 PanScan, 16:9  |
| <b>Video Resolution</b> | 720x576i, 720x576p, 720x480i, 720x480p, 1280x720p, 1920x1080i, 1920x1080p (HDMI Only) |
| <b>Audio Decoding</b>   | AC3, MPEG-1 Layer I/II, MPEG-2 Layer II   |
| <b>Audio Mode</b>       | Streo/Joint stereo/Mono, Dolby AC3  |
| <b>Sampling Rate</b>    | 32KHz, 44.1KHz and 48KHz  |

#### \* Main System

|                       |  |
|-----------------------|--|
| <b>Main Processor</b> | Sti Chipset  |
| <b>Memory</b>         | Flash-ROM : 32 MBytes<br>SDRAM : 256 MBytes (DDR2)<br>EEPROM : 256 Bytes |

#### \* Audio / Video & Data IN/OUT

|                 |  |
|-----------------|--|
| <b>TV SCART</b> | RGB, Y/C, CVBS Video, Audio L, R Output        |
| <b>RCA</b>      | CVBS Video Output, Audio L, R Output           |
| <b>HDMI</b>     | Video & Audio Output                           |
| <b>Optic</b>    | AC3 Dolby Digital (SPDIF)                      |
| <b>USB</b>      | USB 2.0 Host Support (Front & Rear)            |
| <b>Ethernet</b> | RJ45 connector, 10/100M Base                   |
| <b>RS-232C</b>  | 9 pin D-SUB (Male) type, Transfer rate 115Kbps |

#### \* Front Panel

|                |   |
|----------------|---|
| <b>Slot</b>    | 1 USB 2.0 Host Slot<br>2 Common Interface PCMCIA slots<br>1 Smart Card Slot |
| <b>Display</b> | 7-Segment (4 Digit)   |
| <b>Buttons</b> | 3 Buttons(Standby, CH UP/DOWN)  |

#### \* Power Supply

|                          |  |
|--------------------------|--|
| <b>Input Voltage</b>     | AC 100 ~ 250V, 50/60Hz                       |
| <b>Type</b>              | SMPS   |
| <b>Power Consumption</b> | Max. 30W                                     |
| <b>Standby Power</b>     | Max. 1W                                      |
| <b>Protection</b>        | Separate Internal Fuse & Lighting protection |

#### \* Physical Specification

|                         |                      |
|-------------------------|----------------------|
| <b>Size (W x H x D)</b> | 260mm X 43mm X 180mm |
| <b>Weight (Net)</b>     | 1.1 Kg               |
| <b>Operating Temp.</b>  | 0°C ~ +45°C          |
| <b>Storage Temp.</b>    | -10°C ~ +70°C        |

